



Image shown may not reflect actual package.

## STANDBY

**1280 e kW 1600 kVA  
50 Hz 1500 rpm 400 Volts**

Caterpillar is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

## FEATURES

### EMISSIONS / FUEL STRATEGY

- Low Emissions

### FULL RANGE OF ATTACHMENTS

- Wide range of bolt-on system expansion attachments, factory designed and tested

### WORLDWIDE PRODUCT SUPPORT

- Caterpillar® dealers provide extensive post sale support including maintenance and repair agreements
- Caterpillar dealers fill 99.7% of parts orders within 24 hours
- Caterpillar dealers have over 1,844 dealer branch stores operating in 166 countries
- The Cat Scheduled Oil Sampling program cost effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by-products

### DESIGN CRITERIA

- The generator set accepts rated load in one step

### CAT 3512B TA DIESEL ENGINE

- Reliable, rugged, durable design
- Field-proven in thousands of applications worldwide
- Four-stroke-cycle diesel engine combines consistent performance and excellent fuel economy with minimum weight

### CAT SR4B GENERATOR

- Matched to the performance and output characteristics of Caterpillar engines
- Optimum winding pitch for minimum total harmonic distortion and maximum efficiency
- Single point access to accessory connections
- UL 1446 recognized Class H insulation

### CAT EMCP3 CONTROL PANELS

- Controls designed to meet individual customer needs:
- EMCP 3 provides the option for full-featured power metering and protective relaying
- Segregated low voltage, AC/DC accessory box provides single point access to accessory connections

# STANDBY 1280 kW 1600 kVA

50 Hz 1500 rpm 400 Volts



## FACTORY INSTALLED STANDARD & OPTIONAL EQUIPMENT

System	Standard	Optional
Air Inlet	<ul style="list-style-type: none"> <li>• Single element canister type air cleaner</li> <li>• Service indicator</li> </ul>	<ul style="list-style-type: none"> <li>• Dual element &amp; heavy duty air cleaners (with pre-cleaners)</li> <li>• Air inlet adapters &amp; shutoff</li> </ul>
Cooling	<ul style="list-style-type: none"> <li>• Radiator with guard (43°C)</li> <li>• Low Profile (frontal area)</li> <li>• Low Airflow</li> <li>• Fan and belt guards</li> <li>• Radiator duct flange</li> <li>• Coolant drain line with valve</li> <li>• Fan and belt guards</li> <li>• Caterpillar Extended Life Coolant*</li> </ul> <p>*Not included with packages without radiators</p>	<ul style="list-style-type: none"> <li>• Radiator with 27°C 50°C ambient capability</li> <li>• Radiator option for 57°C ambient with treated water</li> <li>• Radiator removal</li> <li>• Heat exchanger and expansion tank</li> <li>• Heavy duty, harsh environment radiator at 43°C and 50°C</li> <li>• Coolant level switch gauge</li> <li>• Jacket water heater</li> </ul>
Exhaust	<ul style="list-style-type: none"> <li>• Dry exhaust manifold</li> <li>• Flanged faced outlets</li> </ul>	<ul style="list-style-type: none"> <li>• Mufflers and silencers</li> <li>• Stainless steel exhaust flex fittings</li> <li>• Elbows, flanges, expanders &amp; Y adapters</li> </ul>
Fuel	<ul style="list-style-type: none"> <li>• Secondary fuel filters</li> <li>• Fuel priming pump</li> <li>• Flexible fuel lines</li> <li>• Fuel cooler*</li> </ul> <p>*Not included with packages without radiators</p>	<ul style="list-style-type: none"> <li>• Water separator</li> <li>• Duplex fuel filter</li> </ul>
Generator	<ul style="list-style-type: none"> <li>• Permanent magnet excited</li> <li>• Class H insulation</li> <li>• Class F temperature (105°C prime/130°C standby)</li> <li>• Winding temperature detectors (select models)</li> <li>• Anti-condensation space heaters</li> </ul>	<ul style="list-style-type: none"> <li>• Oversize &amp; premium generators</li> </ul>
Power Termination	<ul style="list-style-type: none"> <li>• Bus bar (NEMA and IEC mechanical lug holes)- right side standard</li> <li>• Top and bottom cable entry</li> </ul>	<ul style="list-style-type: none"> <li>• Circuit breakers, UL listed, 3 pole shunt trip, 80% or 100% rated, choice of trip units, manual or electrically operated (low voltage only)</li> <li>• Circuit breakers, IEC compliant, 3 or 4 pole with shunt trip (low voltage only), choice of trip units, manual or electrically operated</li> <li>• Shroud cover for bottom cable entry</li> <li>• Power terminations can be located on the left and/or rear as an option. Also, multiple circuit breakers can be ordered (up to 3)</li> </ul>
Governor	<ul style="list-style-type: none"> <li>• ADEM™ III</li> </ul>	<ul style="list-style-type: none"> <li>• Load share module</li> </ul>
Control Panel	<ul style="list-style-type: none"> <li>• User interface panel (UIP) - rear mount</li> <li>• EMCP 3.1 Genset Controller</li> <li>• Voltage and Speed Adjust</li> <li>• AC&amp;DC customer wiring area (right side)</li> <li>• CAT digital voltage regulator (CDVR)with DVAR/PF control, 3-phase sensing</li> <li>• Reactive droop</li> <li>• Emergency Stop Pushbutton</li> </ul>	<ul style="list-style-type: none"> <li>• EMCP 3.3</li> <li>• Option for right or left mount UIP</li> <li>• Option for rear or left mount Customer wiring area</li> <li>• Local &amp; remote annunciator modules</li> <li>• Load share module</li> <li>• Discrete I/O Module</li> <li>• Generator temperature monitoring &amp; protection</li> </ul>
Lube	<ul style="list-style-type: none"> <li>• Lubricating oil and filter</li> <li>• Oil drain line with valves</li> <li>• Fumes disposal</li> <li>• Gear type lube oil pump</li> </ul>	<ul style="list-style-type: none"> <li>• Oil level regulator</li> <li>• Deep sump oil pan</li> <li>• Electric &amp; air prelube pumps</li> <li>• Manual prelube with sump pump</li> <li>• Duplex oil filter</li> </ul>
Mounting	<ul style="list-style-type: none"> <li>• Structural steel tube</li> <li>• Anti-vibration mounts (shipped loose)</li> </ul>	<ul style="list-style-type: none"> <li>• Isolator removal</li> <li>• Spring-type zone 4</li> </ul>
Starting/Charging	<ul style="list-style-type: none"> <li>• 24 volt starting motor(s)</li> <li>• Batteries with rack and cables</li> <li>• Battery disconnect switch</li> </ul>	<ul style="list-style-type: none"> <li>• Battery chargers (10 &amp; 20 Amp)</li> <li>• 45 amp charging alternator</li> <li>• Oversize batteries</li> <li>• Ether starting aids</li> <li>• Heavy duty starting motors</li> <li>• Barring device (manual)</li> <li>• Air starting motor with control &amp; silencer</li> </ul>
Note	<p>Standard and optional equipment may vary for UL 2200 Listed Packages. UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics.</p>	

## SPECIFICATIONS

### CAT GENERATOR

SR4B Generator

Frame size.....	824
Excitation.....	Permanent Magnet
Pitch.....	0.6667
Number of poles.....	4
Number of bearings.....	Single Bearing
Insulation.....	UL 1446 Recognized Class H with tropicalization and antiabrasion
IP rating.....	Drip Proof IP22
Alignment.....	Pilot Shaft
Overspeed capability - % of rated.....	180
Wave form.....	003.00
Paralleling kit/Droop transformer.....	Standard
Voltage regulator.....	3 Phase sensing with selectable volts/Hz
Voltage regulation.....	Less than +/- 1/2% (steady state)
	Less than +/- 1% (no load to full load)
Telephone Influence Factor.....	Less than 50
Harmonic distortion.....	Less than 5%

### CAT DIESEL ENGINE

3512B TA, 4-stroke-cycle watercooled diesel

Bore - mm.....	170.00 mm (6.69 in)
Stroke - mm.....	190.00 mm (7.48 in)
Displacement - L.....	51.80 L (3161.03 in <sup>3</sup> )
Compression ratio.....	13.0:1
Aspiration.....	TA
Fuel system.....	Electronic unit injection
Governor type.....	ADEM3

### CAT EMCP3 CONTROLS

- EMCP 3.1 (standard)
- EMCP 3.3 (optional)
- Integral to generator terminal box
- IP 23 enclosure
- UL/CSA/CE
- Electronically dead front
- Lockable hinged door (optional)
- Run/Auto/Stop/Control
- Voltage Adjust (Optional on 3.1)
- True RMS metering, 3-phase
- Digital indications for:
  - RPM
  - Operating hours
  - Oil pressure
  - Coolant temperature
  - System DC volts
  - AC volts, phase amps, Hz
  - L-L volts, L-N volts, Phase amps, Hz
  - ekW, kVA, kVAR, kWhr, %kW, PF(\*)
- Shutdowns with indicating lights (with optional Annunciator)
  - Low oil pressure
  - High coolant temperature
  - Overspeed
  - Emergency stop
  - Failure to start (over crank)
- Programmable protective relaying functions:(\*)
  - Under and over voltage
  - Under and over frequency
  - Reverse power
  - Overcurrent
- MODBUS isolated data link (RS-485 half-duplex)supports serial communication at data rate up to 1115.2 kbaud (\*)

**TECHNICAL DATA**

Open Generator Set - - 1500 rpm/50 Hz/400 Volts	DM8178	
<b>Low Emissions</b>		
<b>Generator Set Package Performance</b> Genset Power rating @ 0.8 pf Genset Power rating with fan	1600 kVA 1280 kW	
<b>Coolant to aftercooler</b> Coolant to aftercooler temp max	90 ° C	194 ° F
<b>Fuel Consumption</b> 100% load with fan 75% load with fan 50% load with fan	336.5 L/hr 257.0 L/hr 182.3 L/hr	88.9 Gal/hr 67.9 Gal/hr 48.2 Gal/hr
<b>Cooling System<sup>1</sup></b> Ambient air temperature Air flow restriction (system) Air flow (max @ rated speed for radiator arrangement) Engine coolant capacity	48 ° C 0.12 kPa 1614 m <sup>3</sup> /min 156.8 L	118 ° F 0.48 in. water 56998 cfm 41.4 gal
<b>Inlet Air</b> Combustion air inlet flow rate	102.2 m <sup>3</sup> /min	3609.2 cfm
<b>Exhaust System</b> Exhaust stack gas temperature Exhaust gas flow rate Exhaust flange size (internal diameter) Exhaust system backpressure (maximum allowable)	474.6 ° C 269.8 m <sup>3</sup> /min 203.2 mm 6.7 kPa	886.3 ° F 9527.9 cfm 8.0 in 26.9 in. water
<b>Heat Rejection</b> Heat rejection to coolant (total) Heat rejection to exhaust (total) Heat rejection to aftercooler Heat rejection to atmosphere from engine Heat rejection to atmosphere from generator	568 kW 1231 kW 262 kW 146 kW 50.6 kW	32302 Btu/min 70007 Btu/min 14900 Btu/min 8303 Btu/min 2877.6 Btu/min
<b>Alternator<sup>2</sup></b> Motor starting capability @ 30% voltage dip Frame Temperature Rise	2626 skVA 824 105 ° C	221 ° F
<b>Lube System</b> Sump refill with filter	310.4 L	82.0 gal
<b>Emissions (Nominal)<sup>3</sup></b> NOx mg/nm <sup>3</sup> CO mg/nm <sup>3</sup> HC mg/nm <sup>3</sup> PM mg/nm <sup>3</sup>	3883.0 mg/nm <sup>3</sup> 600.8 mg/nm <sup>3</sup> 53.8 mg/nm <sup>3</sup> 26.2 mg/nm <sup>3</sup>	

<sup>1</sup> Ambient capability at 300 m (984ft) above sea level. For ambient capability at other altitudes, consult your Caterpillar dealer.

<sup>2</sup> UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics. Generator temperature rise is based on a 40 degree C ambient per NEMA MG1-32.

<sup>3</sup> Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77°F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

# STANDBY 1280 kW 1600 kVA

50 Hz 1500 rpm 400 Volts



## RATING DEFINITIONS AND CONDITIONS

---

**Meets or Exceeds International Specifications:** ABGSM TM3, AS1359, AS2789, BS4999, BS5000, BS5514, DIN6271, DIN6280, EGSA101P, IEC34/1, ISO3046/1, ISO8528, JEM1359, NEMA MG 1-22, VDE0530, 89/392/EEC, 89/336/EEC

**Standby** - Output available with varying load for the duration of the interruption of the normal source power. Standby power in accordance with ISO8528. Fuel stop power in accordance with ISO3046/1, AS2789, DIN6271, and BS5514. Standby ambients shown indicate ambient temperature at 100 percent load which results in a coolant top tank temperature just below the shutdown temperature.

**Ratings** are based on SAE J1995 standard conditions. These ratings also apply at ISO3046/1, DIN6271, and BS5514 standard conditions.

**Fuel Rates** are based on fuel oil of 35° API (16° C or 60° F) gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.).

**Additional Ratings** may be available for specific customer requirements. Consult your Caterpillar representative for details.

# STANDBY 1280 ekW 1600 kVA

50 Hz 1500 rpm 400 Volts



## DIMENSIONS

---

Package Dimensions		
Length	5097.8 mm	200.7 in
Width	2035.0 mm	80.12 in
Height	2367.2 mm	93.2 in
Weight	14 025 kg	30,920 lb

Note: Do not use for installation design.  
See general dimension drawings for detail (Drawing #2748716).

Performance No.: DM8178

Feature Code:: 512DE4P

Source:: U.S. Sourced

12 May 2006

6872852

[www.CAT-ElectricPower.com](http://www.CAT-ElectricPower.com)

© 2006 Caterpillar  
All rights reserved.

Materials and specifications are subject to change without notice.  
The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, their respective logos and "Caterpillar Yellow," as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.